

A-Frame System

The A-Frame System provides a secure anchor point on a portable structure to give workers increased coverage and protection. Depending on the configuration, this system has the capacity to provide fall protection for up to two workers and can be easily moved from job site to job site, providing safe and reliable fall protection where you need it. These systems are ANSI, OSHA and CE compliant.

ADDITIONAL A-FRAME OPTIONS:

- 8 in. (0.2m) Urethane Wheel Set
- Power Lifting Kit
- Custom Paint Job
- Tag Line Assist
- Pull Handle
- Fold-Out Outriggers
- Tow Bar



FIXED HEIGHT SYSTEMS

- Provide effective/economical means of anchoring overhead
- Each system contains one rail with two trolleys
- Ideal in areas with no overhead obstructions or door height restrictions
- System includes heavy-duty leveling jacks

ANCHOR HEIGHT	RAIL WIDTH	WHEELS	# OF USERS	PART #
15 ft. (4.6m)	15 ft. (4.6m)	16 in. (0.4m) Caster	2	8517790
15 ft. (4.6m)	20 ft. (6.1m)	16 in. (0.4m) Caster	2	8517791
15 ft. (4.6m)	30 ft. (9.1m)	16 in. (0.4m) Caster	2	8517792
20 ft. (6.1m)	15 ft. (4.6m)	16 in. (0.4m) Caster	2	8517793
20 ft. (6.1m)	20 ft. (6.1m)	16 in. (0.4m) Caster	2	8517794
20 ft. (6.1m)	30 ft. (9.1m)	16 in. (0.4m) Caster	2	8517795
30 ft. (9.1m)	15 ft. (4.6m)	16 in. (0.4m) Caster	2	8517796
30 ft. (9.1m)	20 ft. (6.1m)	16 in. (0.4m) Caster	2	8517797
30 ft. (9.1m)	30 ft. (9.1m)	16 in. (0.4m) Caster	2	8517798



ADJUSTABLE HEIGHT SYSTEMS

- Can be adjusted using overhead crane, forklift or powered systems
- Each system contains two rails for bypassing trolleys
- Ideal in areas with overhead obstructions and door height limitations where lowering the overall height of the A-Frame is a requirement
- System includes heavy-duty leveling jacks

ANCHOR HEIGHT	RAIL WIDTH	WHEELS	# OF USERS	PART #
16-22.5 ft. (4.9-6.9m)	20 ft. (6.1m)	16 in. (0.4m) Pneumatic	2	8517780
16-22.5 ft. (4.9-6.9m)	30 ft. (9.1m)	16 in. (0.4m) Pneumatic	2	8517781

